MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	CHOTEAU (4U5)	AIRPORT REFERENCE CODE:	B-I (SM)
CITY:	CHOTEAU	APPROACH TYPE:	NPI
CONTACT:	JOHN NORDHAGEN	DATE INVENTORIED:	1-25-96
PHONE #:	466-2968	INSPECTED BY:	RSD

	REQUIRED	ACTUAL	ALP	CONFORM
RUNWAY 5/23 INVENTORY				
DISTANCE TO:				
HOLD LINES FROM CENTERLINE:	125'	90'		NO
PARALLEL TAXIWAY FROM CENTERLINE:	150'	N/A		N/A
AIRCRAFT PARKING FROM CENTERLINE:	125'	OK		✓
RUNWAY WIDTH:	60'	58-59		OK
RUNWAY LENGTH:	5,350(1)		3,800'	<75%
RUNWAY SAFETY AREA (RSA) WIDTH:	120'	(2)&(3)		NO
RUNWAY OBJECT FREE AREA (OFA) WIDTH:	250'	(4)		NO
PRIMARY / TRANSITION SURFACE PENETRATIONS:	250' W & 7:1	(4) - (6)		NO
LONGITUDINAL GRADE - SITE DIST. PROBLEMS:		OK		✓ ✓
OBSTACLE FREE ZONE ANALYSIS:	250' WIDE x 20	00' BEYOND		(4)
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"	FLUSH - 1	"	NO
PAVEMENT MARKING TYPE:	NPI	BASIC		NO
PAVEMENT MARKING CONDITION:		GOOD		N/A
RUNWAY 5 END INVENTORY				
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'	(7)		NO
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'	(7)		NO NO
APPROACH OBSTRUCTIONS:	20:1	NONE		
RUNWAY END ELEVATION:	20.1	NONE	3,946.0	N/A
ROMMAT END ELEVATION.			3,340.0	IN/A
RUNWAY23_ END INVENTORY				
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'	OK		✓
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'	OK		✓ /
APPROACH OBSTRUCTIONS:	20:1	NONE		✓
RUNWAY END ELEVATION:			3,935.0	N/A
RUNWAY LIGHTING INVENTORY				
DISTANCE FROM PAVEMENT EDGE:	10'	10'		
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'	OK (8)		NO
TYPE:		MOUNTED, CRO	DUSF-HINDS	N/A
CONDITION:	17.17.2	FAIR		N/A
COLOR:	WHITE	WHITE		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	******	'*****		
THRESHOLD 5	4.01	4.01		
DISTANCE FROM PAVEMENT EDGE:	10'	10'		
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'	10'		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
COLOR:	RED/GREEN	RED/GREEN	N	
THRESHOLD 23				
DISTANCE FROM PAVEMENT EDGE:	10'	10'		/
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'	10'		/
COLOR:	RED/GREEN	RED/GREEN	1	✓

COMMENTS: (1) R/W LENGTH OF 3,860' FOR 75%, 5,010' FOR 95% AND 5,350' FOR 100% COVERAGE; ALP ULT OF 5,100' SHOWN

- (2) STEEP DROP OFF 100' DIRECTLY SOUTH OF RUNWAY END 5
- (3) CULVERT ENDS UNDER TAXIWAY AND ANOTHER 450' FROM 23 END IN RSA 100', 135', 57' AND 72' FROM RW CL
- (4) FENCE 100' FROM CL AT 5 END IN OFA AND PRIMARY SURFACE
- (5) ANTENNA ON HANGAR SOUTH OF RW PENETRATES TRANSITIONAL SURFACE (23%)
- (6) FIVE TREES NEAR ROAD SOUTH OF RUNWAY MAY BE IN TRANS. SURFACE, UNABLE TO DETERMINE BECAUSE OF GRADE
- (7) BANK @ 190'-200' DROPS OFF STEEPLY TO ROAD IN OFA; HOWEVER ROAD IS BELOW RW GRADE
- (8) THREE MISSING RUNWAY LIGHTS

MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	CHOTEAU (4U5)	AIRPORT REFERENCE CODE:	B-I (SM)
CITY:	CHOTEAU	APPROACH TYPE:	VISUAL
CONTACT:	JOHN NORDHAGEN	DATE INVENTORIED:	1-25-96
PHONE #:	466-2968	INSPECTED BY:	RSD

	REQUIRED	ACTUAL	ALP	CONFORM
TAXIWAY INVENTORY				
TAXIWAY WIDTH:	25'	29'		✓
TAXIWAY SAFETY AREA WIDTH:	49	OK		✓
TAXIWAY OBJECT FREE AREA WIDTH:	89	OK		✓
DIST. FROM CENTERLINE TO FIXED OR MOVEABLE OBJ.	44.5	OK		✓
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"	1.5"+		✓
PAVEMENT MARKING TYPE:		YELLOW		✓
PAVEMENT MARKING CONDITION:		GOOD		N/A
TAXIWAY LIGHTING INVENTORY		(1)		N/A
DISTANCE FROM PAVEMENT EDGE:	10'	NONE		
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'	1		
TYPE:				
CONDITION:				
COLOR:	BLUE	•		

TYPE OF BEACON:	MOUNTED ON MAIN HANGAR IN SW CORNER OF APRON

SIZE OF BEACON: 12"

MISCELLANEOUS

OTHER LIGHTING AIDS (VASI,PAPI,REIL): NONE

WINDCONE (CONDITION & COMPLIANCE): SOUTH OF RW ~300', LIGHTED, ~25', POOR COND, SOCK COND OK

SEGMENTED CIRCLE (CONDITION & COMPLIANCE): METAL PANEL CONSTRUCTION, NO PAINT REMAINING

WINDCONE (CONDITION & COMPLIANCE): WIND CONE ON SOUTH END OF T-HANGAR

SEGMENTED CIRCLE (CONDITION & COMPLIANCE): NONE

FENCING: NONE

SIGNS: (TYPE, CONDITION, PLACEMENT) NONE

COMMENTS:
(1) ENTRANCE BLUE LIGHT SINGLES MARKING EXIT ONLY